














## Tabulka nosností – řetězové vázací prostředky G8 dle EN 818-4

Jistící faktor	1-pramenné řetězy		2-pramenné řetězy				3- a 4-pramenné řetězy		věncové řetězy	Smyčkové závěsy (úvazy)				Použitelné pro jednoduché háky pro 1-   2-   3- a   4- pramenné řetězy			
																	
4																	
Úhel sklonu	-	-	do 45°	45°- 60°	do 45°	45°- 60°	do 45°	45°- 60°		do 45°	do 45°	do 45°	do 45°				
Faktor zatížení	1	0,8	1,4	1	1,12	0,8	2,1	1,5	1,6	1,4	2,1	1	1,4				
Kód	d	Nosnost (kg)															
Ni 5	5	800	640	1.120	800	900	640	1.600	1.180	1.250	1.120	1.600	800	1.120	1,6	1,6	2,5
Ni 6	6	1.120	900	1.600	1.120	1.250	900	2.360	1.700	1.800	1.600	2.360	1.120	1.600	2,5	2,5	5
Ni 7	7	1.500	1.200	2.120	1.500	1.700	1.200	3.150	2.240	2.500	2.120	3.150	1.500	2.120	2,5	2,5	6
Ni 8	8	2.000	1.600	2.800	2.000	2.240	1.600	4.250	3.000	3.150	2.800	4.250	2.000	2.800	2,5	5	6
Ni 10	10	3.150	2.500	4.250	3.150	3.550	2.500	6.700	4.750	5.000	4.250	6.700	3.150	4.250	5	6	8
Ni 13	13	5.300	4.250	7.500	5.300	5.900	4.250	11.200	8.000	8.500	7.500	11.200	5.300	7.500	6	8	10
Ni 16	16	8.000	6.300	11.200	8.000	9.000	6.300	17.000	11.800	12.500	11.200	17.000	8.000	11.200	8	10	16
Ni 19	19	11.200	8.950	16.000	11.200	12.500	8.950	23.600	17.000	18.000	16.000	23.600	11.200	16.000	10	16	32
Ni 22	22	15.000	12.000	21.200	15.000	17.000	12.000	31.500	22.400	23.600	21.200	31.500	15.000	21.200	16	25	32
Ni 26	26	21.200	16.950	30.000	21.200	23.700	16.950	45.000	31.500	33.500	30.000	45.000	21.200	30.000	25	32	32
Ni 32	32	31.500	25.200	45.000	31.500	35.200	25.200	67.000	47.500	50.000	45.000	67.000	31.500	45.000	32	32	50